

**MCGINN & GIBB, PLLC**  
**A PROFESSIONAL LIMITED LIABILITY COMPANY**  
**PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW**  
**8321 OLD COURTHOUSE ROAD, SUITE 200**  
**VIENNA, VIRGINIA 22182-3817**  
**TELEPHONE (703) 761-4100**  
**FACSIMILE (703) 761-2375; (703) 761-2376**

**APPLICATION  
FOR  
UNITED STATES  
LETTERS PATENT**

**APPLICANT:** Takakyuki Kamei

**FOR:** BROADCAST PROGRAM SEARCH  
METHOD IN DIGITAL  
BROADCASTING RADIO RECEIVING  
APPARATUS, AND  
COMPUTER READABLE  
RECORDING MEDIUM RECORDING  
BROADCAST PROGRAM SEARCH  
PROGRAM

**DOCKET NO.:** SON-0515US

0992858-10104  
TOTAL 85822660

- 1 -

**BROADCAST PROGRAM SEARCH METHOD IN DIGITAL BROADCASTING  
RADIO RECEIVING APPARATUS, AND COMPUTER-READABLE RECORDING  
MEDIUM RECORDING BROADCAST PROGRAM SEARCH PROGRAM**

5

**BACKGROUND OF THE INVENTION**

**FIELD OF THE INVENTION:**

The present invention relates to a broadcast program search method in a broadcast receiving apparatus for receiving a broadcast wave centering around DAB (Digital Audio Broadcasting) carried out in Europe, i.e., a broadcast wave which multiplexes a plurality of broadcast programs each containing audio data and broadcast program information and, more particularly, to a broadcast program search method in a digital broadcasting radio receiving apparatus by which a user can efficiently find a desired broadcast program, and a computer-readable recording medium recording a broadcast program search program.

**DESCRIPTION OF THE PRIOR ART:**

Japanese Unexamined Patent Publication No. 10-107669 describes an example of a broadcast receiving apparatus for receiving a broadcast wave such as DAB, i.e., a broadcast wave which multiplexes a plurality of broadcast programs each containing audio data and broadcast program information. In the DAB broadcasting system, several broadcast programs (called services) are multiplexed on a

09972858 101001

certain frequency (called an ensemble), and several different broadcast contents (called service components) are contained in these broadcast programs.

As shown in Fig. 1, a conventional broadcast receiving apparatus includes a DAB receiver 1, a microcomputer controller 2 for controlling the DAB receiver 1, an input unit 3 operated by a user, and a display unit 4 by which the user checks the state of reception. The microcomputer controller 2 comprises a CPU 7 and a memory 8. The CPU 7 executes programs stored in the memory 8 to control the input unit 3, the display unit 4, and the DAB receiver 1. Of these programs, a DAB control program 5 for controlling the DAB receiver 1 contains a broadcast program search program 6 in the prior art (Japanese Unexamined Patent Publication No. 10-107669).

This conventional broadcast receiving apparatus having the above arrangement operates as follows.

To find a desired broadcast program, a user presses a key or the like on the input unit 3 to switch broadcast programs one after another, and checks each broadcast program by a sound generated from a loudspeaker or information displayed on the display unit. The user repeats this operation until he or she finds the desired program.

Unfortunately, this prior art has the following

09972858-101001

problems.

That is, as described above, to find a desired broadcast program, a user presses a key or the like to switch broadcast programs one after another, and checks  
5 each broadcast program by a sound generated from a loudspeaker or information displayed on the display unit. In the DAB broadcasting system, however, a plurality of broadcast programs each containing audio data and broadcast program information are multiplexed. Therefore,  
10 to find a desired broadcast program by, e.g., a program type (to be abbreviated as a PTY hereinafter) as one broadcast program information, it is necessary, owing to the DAB format, to search as many as 16,384 program types (6 bits of a coarse code and 8 bits of a fine code, a  
15 total of  $2^{14} = 16,384$ ). This operation is difficult and cumbersome.

Also, the conventional broadcast receiving apparatus with the above arrangement requires the following operation. That is, a user previously designates PTYs  
20 which he or she habitually listens to. From these previously designated PTYs, the user selects a PTY which he or she currently wants to search for or listen to, and searches for a broadcast program matching the selected PTY, by using the broadcast program search program 6 (a  
25 broadcast program searching means 56 in Japanese

0972858 101001  
100101" 8582650

Unexamined Patent Publication No. 10-107669).

Unfortunately, the search item is limited to a PTY. Therefore, if the broadcast program desired by the user is not found as a result of search, the user may be forced to  
5 perform the aforementioned cumbersome operation.

Program types are, e.g., music, news, sport, and drama, and they are sometimes classified more finely. As an example, music is classified into classic, jazz, popular, and the like.

10

#### SUMMARY OF THE INVENTION

The present invention has been made to solve the above problems of the prior art, and has as its object to provide a broadcast program search method in a digital broadcasting radio receiving apparatus by which a user can  
15 efficiently find a desired broadcast program, and a computer-readable storage medium recording a broadcast program search program.

To achieve the above object, a broadcast program search method in a digital broadcasting radio receiving  
20 apparatus of the present invention is a broadcast program search method in a digital broadcasting radio receiving apparatus which comprises a DAB receiver which receives a DAB digital signal and transfers broadcast program information data in the digital signal to a microcomputer  
25 controller, an input unit operated by a user, a CPU for

09972558-101001

executing a stored program, a memory for storing a program,  
a microcomputer controller which receives the broadcast  
program information data and executes control by the  
program, a display unit for checking the state of each DAB  
5 broadcast station program, a DAB control program which  
controls the DAB receiver and analyses the broadcast  
program information data from the DAB receiver, and a  
broadcast program search program which starts operation  
upon a key operation of a user, characterized by  
10 comprising the step of activating the broadcast program  
search program and switching to a broadcast program search  
mode, the step of selecting a search item and setting the  
search condition of the search item by an operation by a  
user, the search step of performing search by the search  
15 item selected by the user on the basis of the selection of  
the search item and the set search condition of the search  
item, the channel selection step of selecting a channel on  
the basis of the search result in the search step, and the  
step of checking whether to again perform search if the  
20 search is unsuccessful, repeating the setting under the  
set search condition if search is to be again performed,  
and terminating the broadcast program search program if no  
search is to be again performed.

A computer-readable storage medium recording a  
25 broadcast program search program of the present invention

09072858-101001

is a computer-readable storage medium recording a broadcast program search program for a digital broadcasting radio receiving apparatus which comprises a DAB receiver, a microcomputer controller which includes a CPU and a memory and controls the DAB receiver, an input unit operated by a user, a display unit for checking the state of reception, a program which is stored in the memory and controls the input unit, the display unit, and the DAB receiver, and a DAB control program which contains a broadcast program search program and controls the DAB receiver, characterized by comprising the process of activating the broadcast program search program and switching to a broadcast program search mode, the process of selecting a search item and setting the search condition of the search item by an operation by a user, the search process of performing search by the search item selected by the user on the basis of the selection of the search item and the set search condition of the search item, the channel selection process of selecting a channel on the basis of the search result in the search process, and the process of checking whether to again perform search if the search is unsuccessful, repeating the setting under the set search condition if search is to be again performed, and terminating the broadcast program search program if no search is to be again performed.

09972858.101001  
FOOTNOTES

09972858 101001

The effect of the present invention is obvious from the above aspects. For example, if X types of PTYs, Y types of service labels, and Z types of service component labels are used, search takes about a few minutes when it  
5 is performed by checking sounds and displays. However, when the search method of the present invention is used, search can be performed within a few tens of seconds. Also, a user need only perform key operations several times. This eliminates the need to perform a cumbersome  
10 operation, by which a user operates keys to find a desired broadcast program, which is the problem of the prior art.

In addition, a routine for storing search conditions in a memory obviates an operation of setting search items. This can release a user from this troublesome operation.  
15 Also, in the present invention, a PTY, a service label, and a service component label are used as search items. Therefore, unlike the conventional search in which the search item is limited to a PTY, a broadcast program desired by a user can be found without omission. Even if  
20 there is an omission, search can be again performed by changing the search conditions. Accordingly, search can be again performed even in a case where no broadcast program can be found by a PTY, which is the problem of the prior art.

25 The above and many other objects, features and



advantages of the present invention will become manifest to those skilled in the art upon making reference to the following detailed description and accompanying drawings in which preferred embodiments incorporating the principle  
5 of the present invention are shown by way of illustrative examples.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the arrangement of an example of a broadcast receiving apparatus used in the  
10 present invention;

Fig. 2 is a flow chart of a broadcast program search program according to the present invention;

Fig. 3 is a flow chart of a search condition setting routine according to the first embodiment of the present  
15 invention;

Fig. 4 is a flow chart of a search routine according to the first embodiment of the present invention;

Fig. 5 is a flow chart of a PTY search routine according to the first embodiment of the present  
20 invention;

Fig. 6 is a flow chart of a service label search routine according to the first embodiment of the present invention;

Fig. 7 is a flow chart of a service component label  
25 search routine according to the first embodiment of the

09072658-101001

present invention;

Fig. 8 is a channel selection routine according to the first embodiment of the present invention;

Fig. 9 is a flow chart of a program information  
5 recording list formation routine according to the second embodiment of the present invention;

Fig. 10 is a flow chart of a search condition setting routine according to the third embodiment of the present invention;

10 Fig. 11 is a view showing the structure of a DAB transmission frame;

Fig. 12 is a view showing the structure of an FIB made up of 256 bits;

Fig. 13 is a view showing the structure of an FIG  
15 whose FIG type is 1(001) shown in Fig. 12;

Fig. 14 is a view showing the structure of a Type 1 field whose Extension is 2 in an FIG data field shown in Fig. 13;

Fig. 15 is a view showing the structure of a Type 1  
20 field whose Extension is 1 in the FIG data field shown in Fig. 13, this Type 1 field containing data indicative of service label data; and

Fig. 16 is a view showing the structure of a Type 1 field whose Extension is 4 in the FIG data field shown in  
25 Fig. 13.

09972858-101001

### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Several preferred embodiments of the present invention will be described below with reference to the accompanying drawings.

5        Fig. 1 is a block diagram of an embodiment of a broadcast receiving apparatus used in the present invention. The broadcast receiving apparatus of this embodiment is a broadcasting receiver which operates by programs. This broadcast receiving apparatus includes a  
10 DAB receiver 1, a microcomputer controller 2, an input unit 3, and a display unit 4. The DAB receiver 1 receives a DAB digital signal and transmits broadcast program information data in the signal to the microcomputer controller 2. The input unit 3 is used by a user to  
15 perform key operations. The microcomputer controller 2 has a CPU 7 for detecting the state of the input unit 3 and executing programs stored in a memory 8. This microcomputer controller 2 operates by these programs. The display unit 4 displays the state of each broadcast  
20 program of DAB. The internal memory 8 of the microcomputer controller 2 contains a DAB control program 5 for, e.g., controlling the DAB receiver 1 and analyzing broadcast program information data from the DAB receiver 1, and a broadcast program search program 6 which starts  
25 operating when a user performs a specific key operation.

09972858 101001

The overall operation of this embodiment will be described in detail below with reference to Fig. 1 and flow charts in Figs. 2 to 8.

First, when a user wishes to find a desired broadcast  
5 program, he or she performs specific key inputting on the  
input unit 3 shown in Fig. 1 to start the operation of the  
broadcast program search program 6 shown in Fig. 1 and  
switch to a broadcast program search mode (step S1 in  
Fig. 2). Next, the operation of a search condition  
10 setting routine 10 is started, and the user performs  
specific key inputting to select search items and set the  
search conditions of these search items. A search item is  
that specific information of a broadcast program, which is  
a condition for searching for the broadcast program.

15 After the search condition setting routine 10 is  
completed, a search routine 11 starts operating to perform  
search on the basis of the search items selected by the  
user. If the search routine 11 finds a broadcast program  
on the basis of the search items selected by the search  
20 condition setting routine 10 (step S2 in Fig. 2), the  
operation of a channel selection routine 12 is started.  
If no broadcast program is found (step S2 in Fig. 2), a  
message for prompting the user to perform a key input  
operation is displayed on the display unit 4 shown in  
25 Fig. 1 to determine whether to again perform search (step

09972858 101001

S3 in Fig. 2). If search is to be again performed (step S3 in Fig. 2), the operation of the search condition setting routine 10 is started. If no search is to be again performed (step S3 in Fig. 2), the broadcast program search program 6 is terminated.

The operation of the search condition setting routine 10 is shown in the flow chart of Fig. 3. In this search condition setting routine 10, the conditions of search concerning a broadcast program desired by the user are set.

10 First, a search condition list and a search result list to be set by the search condition setting routine 10 are initialized (step S10). The search condition list is a storage area for storing search conditions set for individual search items by a setting key (to be described later). When this search condition list is initialized, the operation of the search routine 11 shown in Fig. 2 need not be performed. The search result list is a storage area for storing the results of search by the search routine (to be described later). When this search

15 result list is initialized, the broadcast program search program 6 can be terminated if the search result is NO in step S2, i.e., if the search condition setting routine 11 is interrupted or nothing can be found by the search routine 11.

25 Effective keys in Fig. 3 are a select key for

09972858-104001

selecting a search item, a setting key for setting a search condition for a selected search item, an interrupt key for interrupting the search condition setting routine 10, and a decision key for storing the search condition of each search item and making the search routine 11 operable. In step S11, whether a key is effective is checked. If the key is found to be effective, the operation of the key is performed. If this effective key is the select key, search items are changed (step S12). Examples of the search items are the PTY (a program type, e.g., news, music, and sport) of a broadcast program, a service label (a label which can be attached to a broadcast program), and a service component label (a label which can be attached to each individual broadcast content of a broadcast program). If the effective key is the setting key, the search condition of each search item is set (step S13). For example, if the search item is a PTY, the "program type" of a desired broadcast program is set to "news". If the effective key is the interrupt key, the search condition setting routine 10 is terminated (step S14). If the effective key is the decision key, the search conditions set by the select key and the setting key are stored in the search condition list, and the search condition setting routine 10 is terminated (step S15).

The operation of the search routine 11 is shown in the flow chart of Fig. 4. In this search routine 11, search is performed on the basis of the search conditions set in the search condition setting routine 10. For  
5 example, in Fig. 4 the search items set by the search condition setting routine 10 are a PTY, a service label, and a service component label. In step S20, Flag is set to 0. This Flag is used as determination data to check the matching with the search result list for storing the  
10 search result of each search item, i.e., to check whether to perform step S31 in which identical results for the same search item are removed.

Next, whether to perform PTY search is checked (step S21) by referring to the search condition list stored in  
15 the search condition setting routine 10. If the search is to be performed, a PTY search routine is executed (step S22), and Flag is set to 1 (step S23). After the operation of the PTY search routine is executed (step S22), or if no PTY search is to be performed, whether to perform  
20 service label search is checked (step S24) by referring to the search condition list stored in the search condition setting routine 10. If the search is to be performed, a service label search routine is executed (step S24), and Flag is set to 1 (step S26). After the operation of the  
25 service label search routine is executed (step S24), or if

09972858.101001  
FOOTNOTES 8582660

no service label search is to be performed, whether to perform service component label search is checked (step S27) by referring to the search condition list stored in the search condition setting routine 10. If the search is  
5 to be performed, a service component label search routine is executed (step S28), and Flag is set to 1 (step S29). After the operation of the service component label search routine is executed (step S28), or if no service component label search is to be performed, whether Flag is 1 is  
10 checked (step S30). If YES in step S30, identical results in the search result list are removed (step S31), and the search routine 11 is terminated. If NO in step S30, the search routine 11 is terminated.

The operation of the PTY search routine is shown in  
15 the flow chart of Fig. 5. Broadcast program information on a broadcast wave received by the DAB receiver shown in Fig. 1 contains a plurality of receivable broadcast programs, and a broadcast program matching the PTY search condition is searched for. First, broadcast program  
20 information on a broadcast wave currently being received is searched for the PTY of a receivable broadcast program (step S100). Whether this receivable PTY matches the PTY of the search condition is checked (step S101). If YES in step S101, information pertaining to the receivable PTY is  
25 stored in the search result list (step S102). If NO in

00072858.101001



step S101, the flow advances to step S103. In step S103, whether another searchable receivable PTY exists is checked. If YES in step S103, the flow returns to step S100. If NO in step S103, the PTY search routine is  
5 terminated.

The operation of the service label search routine is shown in the flow chart of Fig. 6.

As explained in the PTY search routine of Fig. 5, broadcast program information on a broadcast wave  
10 currently being received contains a plurality of receivable broadcast programs, and a broadcast program matching the service label search condition is searched for. First, broadcast program information on a broadcast wave currently being received is searched for the service  
15 of a receivable broadcast program (step S110). The label of this receivable service is compared with the service label of the search condition (step S111). If the comparison result is OK, information (SId, label) pertaining to the receivable service is stored in the  
20 search result list. If the comparison result is NG, the flow advances to step S113. In step S113, whether another searchable receivable service exists is checked. If YES in step S113, the flow returns to step S110. If NO in step S113, the service label search routine is terminated.

25 The operation of the service component label search

0972858-101001

As explained in the search routines of Figs. 5 and 6, broadcast program information on a broadcast wave currently being received contains a plurality of receivable broadcast programs, and a broadcast program matching the service component label search condition is searched for. First, broadcast program information on a broadcast wave currently being received is searched for the service component of a receivable broadcast program (step S120). The label of this receivable service component is compared with the service component label of the search condition (step S121). If the comparison result is OK, information (SId, SCId label) pertaining to the receivable service is stored in the search result list. If the comparison result is NG, the flow advances to step S123. In step S123, whether another searchable receivable service component exists is checked. If YES in step S123, the flow returns to step S120. If NO in step S123, the service component label search routine is terminated.

The operation of the channel selection routine 12 is shown in the flow chart of Fig. 8. In this channel selection routine 12, a channel is selected on the basis of the search result list stored in the search routine 11. First, No. is set to 1 (step S40). This No. indicates the number of information to be selected from the search

result list. A channel having this number No. in the search result list is selected (step S41). A selected channel listening time is set (step S42). Whether the search result list records only one program is checked  
5 (step S43). If YES in step S43, the channel selection routine 12 is terminated. If NO in step S43, the flow advances to step S44. In step S44, whether the user has issued a selected channel determination request (a selected channel determination request is, e.g., to press  
10 a specific key if a program broadcast from a loudspeaker is the desired broadcast program). If YES in step S44, the channel selection routine 12 is terminated. If NO in step S44, the flow advances to step S45. In step S45, whether the selected channel listening time has elapsed is  
15 checked. If YES in step S45, the flow advances to step S46. If NO in step S45, the flow returns to step S44. In step S46, 1 is added to No. In step S47, whether the (No. - 1)th broadcast program information in the search result list is the last one is checked. If YES in step S47, the  
20 flow returns to step S40. If NO in step S47, the flow returns to step S41. In this manner, the channels of broadcast programs in the search result list are selected in turn.

The second embodiment of the present invention will  
25 be described in detail below with reference to the

09972858-101001

accompanying drawings. Referring to a flow chart of a program information recording list formation routine shown in Fig. 9, the embodiment comprises step S200 for forming a program information storage list concerning a PTY, step  
5 S201 for forming a program information storage list concerning a service label, and step S202 for forming a program information storage list concerning a service component label.

The overall operation of this embodiment will be  
10 described in detail below with reference to the flow charts in Figs. 2, 4, 5, 6, 7 and 9.

First, the program information storage list formation routine in Fig. 9 acquires program information pertaining to a PTY, a service label, and a service component label,  
15 during regular broadcasting reception, to be referred to when search is performed in the PTY search routine (step S22), the service label search routine (step S25), and the service component label search routine (step S28) shown in Fig. 4 which is a flow chart of the search routine  
20 shown in Fig. 2. Data of the program information storage list formed by this program information storage list formation routine is compared with the search conditions in step S101 of the PTY search routine in Fig. 5, in step S111 of the service label search routine in Fig. 6, and in  
25 step S121 of the service component label search routine in

09972858-101001

Fig. 7. This improves the search speed and makes it possible to receive a broadcast program desired by a user.

The third embodiment of the present invention will be described in detail below with reference to the accompanying drawings. Fig. 10 is a flow chart of the search condition setting routine 10 in Fig. 2. In this embodiment, step S300 for storing the set contents of search conditions by a search condition set content storage write key and step S301 for reading out the set contents of search conditions by a search condition set content storage read key are added to Fig. 3 of the first embodiment.

Details of the overall operation of this third embodiment will be explained below with reference to the flow chart in Fig. 10. This flow chart shown in Fig. 10 shows the operation of the search condition setting routine 10 in Fig. 2, and performs an operation similar to the flow chart shown in Fig. 3 in the explanation of the first embodiment. In this embodiment, the operations of steps S300 and S301 added to the flow chart in Fig. 3 will be described. In step S11 of Fig. 10, whether a key is an effective key is checked. If the key is an effective key and this effective key is the search condition set content storage write key, a select key and a search condition set by the select key are written in a search condition

09972858-101001

storage list. The search condition storage list is a storage area for storing search conditions. If the effective key is the search condition set content storage read key, the contents of the search condition storage list are written in a search condition list. In this embodiment, a user can store the currently set search condition in the search condition storage list by using the search condition set content write key. For example, if a plurality of search condition set content storage write keys are available, the user can store a plurality of search conditions. To search for a desired broadcast program, the user can set desired search conditions at once by using the search condition set content storage read key. Since no search conditions need be input, search conditions can be efficiently set, i.e., search can be readily performed.

Figs. 11 to 16 illustrate information corresponding to individual search items of the embodiment.

Fig. 11 is a view showing the structure of a DAB transmission frame. This transmission frame has a sync channel, FIC (Fast Information Channel), and MSC (Main Service Channel). The FIC is made up of a plurality of FIBs (Fast Information Blocks), and the MSC is made up of a plurality of CIFs (Common Interleaved Frames). DAB forms a broadcast wave by carrying various pieces of

09972858-101001

information on this transmission frame.

Fig. 12 is a view showing the structure of the FIB. The FIB is composed of 256 bits and has a 30-byte FIB data field and a 16-bit CRC (Cycle Redundancy Check word). The FIB data field is made up of a plurality of FIGs (Fast Information Groups) as a useful data field, End marker, and Padding (an area for byte matching if 30 bytes of the FIG data field are not filled). Each FIG has FIG Type, Length (the bit length of an FIG data field subsequent to Length), and an FIG data field. FIG Type and Length form an FIG header.

Fig. 13 is a view showing the structure of an FIG in Fig. 12 whose FIG Type is 1(001). This FIG is made up of Charset, OE (data indicating whether information in a Type 1 field belongs to this ensemble or another), Extension (the Extension number of FIG Type 1), and the Type 1 field.

Fig. 14 is a view showing the structure of a Type 1 field when Extension in the FIG data field shown in Fig. 13 is 2. This Type 1 field contains Code which is data indicative of PTY data. Data following this Code changes in accordance with a C/F flag (Coarse/Fine flag): if the C/F flag is 0, the data is Coarse code (6 bits); if the C/F flag is 1, the data contains Coarse code and Fine code (8 bits).

Fig. 15 is a view showing the structure of a Type 1

09972858-101001

field when Extension in the FIG data field shown in  
Fig. 13 is 1. This Type 1 field contains service  
identification data (SId) indicating service label data,  
and a character data field (Character field). This  
5 character data field is the service label.

Fig. 16 is a view showing the structure of a Type 1  
field when Extension in the FIG data field shown in  
Fig. 13 is 4. This Type 1 field contains service  
component identification data (SId) indicating service  
10 component data, service identification data (SId), and a  
character data field (Character field). This character  
data field is the service component label.

A computer-readable storage medium recording a  
broadcast program search program of the present invention  
15 will be described below with reference to the accompanying  
drawings.

Referring to Fig. 1, in an environment having a DAB  
receiver 1, a microcomputer controller 2 which controls  
the DAB receiver 1 and includes a CPU 7 and a memory 8, an  
20 input unit 3 operated by a user, and a display unit 4 for  
checking the state of reception, the computer-readable  
storage medium recording the broadcast program search  
program of the present invention is a computer-readable  
storage medium recording a program which is stored in the  
25 memory 8 and controls the input unit 3, the display unit 4,

09972859-101001



and the DAB receiver 1, and the broadcast program search program of the present invention contained in a DAB control program 5 for controlling the DAB receiver 1.

5 A broadcasting receiver which operates by programs includes the DAB receiver 1, the microcomputer controller 2, the input unit 3, and the display unit 4. The DAB receiver 1 receives a DAB digital signal and transmits broadcast program information data in the signal to the microcomputer controller 2. The input unit 3 is used by a user to perform key operations. The microcomputer controller 2 has the CPU 7 for detecting the state of the input unit 3 and executing programs stored in the memory 8. This microcomputer controller 2 operates by these programs. The display unit 4 displays the state of each broadcast program of DAB. The internal memory 8 of the microcomputer controller 2 contains the DAB control program 5 for, e.g., controlling the DAB receiver 1 and analyzing broadcast program information data from the DAB receiver 1, and a broadcast program search program 6 which starts operating when a user performs a specific key operation.

The broadcast program search program 6 is made up of a search condition setting routine 10 for, e.g., selecting a search item for searching for a broadcast program and setting the search condition of the search item, a search

09972858-101001

routine 11 for performing search by using the search item selected by a user, a channel selection routine 12 performed on the basis of the search by the search routine 11, and a control routine for controlling these routines.

5       The search condition setting routine 10 sets search conditions for a broadcast program desired by a user. Search items include a select key for selection, a setting key for setting the search condition of each search item, an interrupt key for interrupting the search condition  
10       setting routine 10, and a decision key for storing the search condition of each search key and making the search routine 11 operable. Examples of the select key are the PTY (a program type, e.g., news, music, and sport) of a broadcast program, a service label (a label which can be  
15       attached to a broadcast program), and a service component label (a label which can be attached to each different broadcast content of a broadcast program).

      The search routine 11 performs search on the basis of the search conditions set by the search condition setting  
20       routine 10. For example, in this embodiment, the search items set by the search condition setting routine 10 are a PTY, a service label, and a service component label. To avoid duplicate search by each selected item, the search condition setting routine 10 removes identical results  
25       from a search result list. In the search routine 11, a

09972858.101001

PTY search routine, a service label search routine, and a service component label search routine are prepared. Broadcast program information on a broadcast wave currently being received contains a plurality of  
5 receivable broadcast programs. The search routine 11 searches these broadcast programs for one which matches the service label search condition.

The channel selection routine 12 selects a channel on the basis of a search result list stored in the search  
10 routine 11. In accordance with a number indicating the number of information to be selected from the search result list, the channel selection routine 12 selects a channel having the number No in the search result list, and sets a selected channel listening time. The channel  
15 selection routine 12 selects the channels of broadcast programs in the search result list in turn.

A description of the operation of the broadcast program search program will be omitted, because the search method using the broadcast program search program of the  
20 digital broadcasting radio receiving apparatus has already been explained in detail with reference to Fig. 1 and the flow charts in Figs. 2 to 8.

The second embodiment of the computer-readable storage medium recording the broadcast program search  
25 program will be described below. This embodiment

09972858-101001

comprises a routine for forming a broadcast program  
information storage list concerning a PTY, a routine for  
forming a broadcast program information storage list  
concerning a service label, and a routine for forming a  
5 broadcast program information storage list concerning a  
service component label. The operation of each routine  
has been described with reference to the flow charts in  
Figs. 2, 4, 5, 6, 7, and 9 in the second embodiment of the  
search method using the broadcast program search program,  
10 so a detailed description thereof will be omitted.

The third embodiment of the computer-readable storage  
medium recording the broadcast program search program will  
be described below.

In this embodiment, a routine for storing the set  
15 contents of a search condition set by a search condition  
set content storage write key and a routine for reading  
out the set contents of a search condition set by a search  
condition set content storage read key are added to Fig. 3  
of the first embodiment of the search method using the  
20 broadcast program search program.

The operation of each routine has been explained with  
reference to the flow chart in Fig. 10 in the third  
embodiment of the search method using the broadcast  
program search program, so a detailed description thereof  
25 will be omitted.

05972858-101001